

## CGM CIGIEMME S.p.A.



Controlli Non Distruttivi - Non Destructive Testing

Product Code 02098050 Ref. no.



### **ATA FLUID A44**

#### PRODUCT DESCRIPTION

Ata Fluid A44 is an excellent anti-foaming, anti-corrosive and wetting liquid concentrate for conditioning aqueous suspensions of magnetic particles. It prevents the formation of algae and bacterial colonies.

#### COMPOSITION

Mixture of liquid non-ionic surfactants, biocides, preservatives and corrosion inhibitors.

N.B.: Like all CGM products, Ata Fluid A44 is tightly controlled to ensure batch uniformity, optimal process verification and control reliability.

#### **SPECIFICATIONS**

- Easy to use.
- Excellent anti-foaming characteristics.
- Excellent wettability of the surface.
- It promotes the dispersion of magnetic particles in the suspension.
- Excellent short-term corrosion inhibition.
- High anti-algae, fungicidal and antibacterial capacity.

#### **PACKAGING TYPE**

- 10 L cans
- 200 L metal drums

#### **APPLICABILITY**

It is ideal for:

- Use in benches with magnetic particle suspension recirculation tanks.
- Use with aqueous suspensions.

#### **INSTRUCTIONS FOR USE**

**TIP:** always operate according to a procedure authorised by a 3<sup>rd</sup> level in Magnetic Particle Inspection.

- Dilute Ata Fluid A44 in bath water (0.5-1.0%), stirring the solution to homogenise it.
- Add the magnetic particles in the amount prescribed by the procedure.
- Shake the suspension for optimal dispersion of the particles.
- Check the concentration of the suspension with the sedimentation glass tube before use.
- Remember that failure to comply with the dilution values may result in excessive foaming.





# CGM CIGIEMME S.p.A.



#### Controlli Non Distruttivi - Non Destructive Testing

#### PROPERTIES AND PRODUCT COMPARISON

	A43	A44	A38	1883
Shape and colour	Milky liquid	Opalescent liquid	Milky liquid	Amber-coloured transparent liquid
Odour	Odourless	Characteristic	Characteristic	Characteristic
Density at 20° EN ISO 12185	1.0 g/cm³	1.0 g/cm³	1.0 g/cm³	1.0 g/cm³
pH ISO 4316	7.5	9	6	9
Solubility	In water	In water	In water	In water

Typical values.

#### RECOMMENDATIONS FOR THE USER

NDT method	Magnetic Particles Inspection	
Shelf life	3 years at a temperature between 5°C and 45°C	
Usage temperature	From -5°C to +55°C	
Dilution	0.5-1.0%	
Magnetic Particles	K35-K40-K150-K755-K31/73	
Preliminary cleaning	Velnet/Solnet	

#### **COMPLIANCE WITH STANDARDS**

- AS 4792

#### **HEALTH AND SAFETY**

Read all health and safety information before using this product. This information can be found in the Safety Data Sheet, available on request.

Rev. 05 - 29/05/2024



